

- + Modular wall sections and corners can be easily assembled to form almost any size/shape spill containment area needed.
- + Heavy-duty, 30 mil, textured polyethylene liner provides rugged, impermeable barrier to capture leaks and spills.
- + Creates large, semi-permanent containment areas. Provides much more gallon capacity than shorter walled containment systems.
- + Versatile system can be easily disassembled for reuse at future sites.
- + Unlike some containment systems, the Ultra-Containment Wall is not secured to the substrate so it is perfect use in parking lots, sand, rocky soil, muddy soil, frozen soil or on concrete areas.
- + Made in the USA. Stock/warehousing: Texas.
- + Meets SPCC, EPA Container Storage Regulation 40 CFR 264.175.

Part#	Wall Height & Description	Dimensions in. (mm)	Weight lbs. (kg)			
8760	1 ft. (0.3 m) - Straight Section	120 x 12 x 12 (3,048 x 305 x 305)	33.0 (15.0)			
8761	1 ft. (0.3 m) - Corner Section	22 x 22 x 12 (559 x 559 x 305)	9.0 (4.0)			
8762	2 ft. (0.6 m) - Straight Section	100 x 24 x 24 (2,540 x 610 x 610)	70.0 (32.0)			
8763	2 ft. (0.6 m) - Corner Section	35 x 30 x 24 (889 x 762 x 610)	26.0 (12.0)			
8764	3 ft. (0.9 m) - Straight Section	72 x 24 x 36 (1,829 x 610 x 914)	60.0 (27.5)			
8765	3 ft. (0.9 m) - Corner Section	30 x 30 x 36 (762 x 762 x 914)	36.0 (16.5)			
8770	30 ml Textured Polyethylene Liner	Custom (per sq. ft./m)	1.0 (0.45)/sq. ft.			
Complete Systems:						

Complete Systems:							
Part#	Wall Height	Usable Dimensions ft. (m)	Item Quantity	Containment Cap. gal. (L)	Weight lbs. (kg)		
8790	1 ft. (0.3 m)	10 x 49 x 1 (3.0 x 14.9 x 0.3)	12-Straight, 4-Corners, 1-Liner (16x55)	1,051 (3,978)	754 (342.0)		
8791	1 ft. (0.3 m)	68 x 68 x 1 (20.7 x 20.7 x 0.3)	28-Straight, 4-Corners, 1-Liner (74x74)	9,194 (34,802)	2,066 (937.1)		
8792	2 ft. (0.6 m)	16 x 55 x 2 (4.9 x 16.8 x 0.6)	18-Straight, 4-Corners, 1-Liner (27x66)	3,623 (13,716)	1,821 (826.0)		
8793	2 ft. (0.6 m)	63 x 63 x 2 (19.2 x 19.2 x 0.6)	32-Straight, 4-Corners, 1-Liner (74x74)	15,874 (60,089)	3,450 (1,564.9)		
8794	3 ft. (0.9 m)	11 x 55 x 3 (3.4 x 16.8 x 0.9)	24-Straight, 4-Corners, 1-Liner (27x71)	3,787 (14,336)	2,157 (978.4)		
8795	3 ft. (0.9 m)	61 x 61 x 3 (18.6 x 18.6 x 0.9)	44-Straight, 4-Corners, 1-Liner (77x77)	22,080 (83,582)	3,958 (1,795.3)		











Molded-in locking pegs allow systems to be setup quickly and easily without the need for special tools or equipment.



Large clips (included) hold the liner in place. Excess liner can be trimmed if desired.